

STATUS RELIEF

Textured decorative paint

STATUS RELIEF is a high-quality relief acrylic coating for exterior surfaces. By using proper rollers it creates numerous decorative textures offering a beautiful, aesthetic result, while providing high protection to applied to the surface. Can be applied after proper preparation on new and old surfaces such as walls, plaster, concrete, brick, wood, chipboard, plasterboard, asbestos cement sheeting, etc. It has strong adhesion and exhibits extremely high resistance to harsh weather conditions. It dries quickly and is absolutely user and environment-friendly. The special formula provides high whiteness and excellent coverage. It is easily applied without leaving streaks and develops high hardness without cracking.



Advantages:

- Environment-friendly and solvent-free.
- Highly water repellent.
- Extremely resistant to sunlight.
- High resistance to adverse atmospheric conditions.
- Strong adhesion.
- Fast drying.
- Excellent coverage.
- High whiteness.
- High workable .
- Spreads easily without steaks.
- High hardness without cracking.



TECHNICAL CHARACTERISTICS

Packaging:



Plastic containers
• 5 Kg
• 15 Kg

Color:



Available in white.

Application:



For exterior and interior use. Walls, plaster, concrete, bricks, ceilings, plasterboards, asbestos cement sheeting , etc.

Storage:



Store in tightly closed container for 24 months of the date of production in a cool and dry place.



Drying time:

- Touch dry 2 h
- Recoating 24 h

*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.

V.O.C. class :



A/c Exterior walls of mineral substrate (W.B) V.O.C limit: 40 gr/lit
Maximum V.O.C of product ready to use product: 39 gr/lit

Application tools:



Special roller.

FIELDS OF APPLICATION

Suitable for exterior application on all common surfaces such as Walls, plaster, concrete, bricks, ceilings, plasterboards, wood, spatula coated surfaces, etc.

SUBSTRATE PREPARATION

Before use, ensure that the surface is clean, dry, robust and free from dust, mold and grease. Remove damaged, or peeling old paint. Where puttying is required, use the STATUS 100% ACRYLIC PUTTY and after drying, sand the surface down and dust well. If there are large cracks, use ready-to-use light white Stucco, STATUS ONE COVER, to fill the cracks applying just one coat without sanding. On new surfaces, first apply one coat of STATUS ACRYLIC PRIMER, or WATER-BASED STATUS DUR. For surfaces covered in fresh plaster or cement, allow the surfaces to dry thoroughly for at least 1 month before painting. For plasterboards and recoating water-base colored surfaces (with white-wash or adhesive) or soiled surfaces (nicotine, soot from heaters, soot, fumes, coffee, juice, graffiti, inks, markers, mildew, mold, moisture, oil, etc.), prime first with solvent-based STATUS DUR, or water-based STATUS DUR primer. Never paint surfaces that may contain moisture. First make sure that the cause of the moisture has stopped and that the surface is completely dry.

APPLICATION

Mix the contents of the container well before use. Apply STATUS RELIEF without diluting it and immediately use the special roller to achieve the desired relief. The surface is recoated with STATUS RELIEF, or acrylic paint. Close the container tightly after use to keep the paint in good condition for future use. You can store undiluted paint in a tightly sealed container for extended periods of time without affecting the quality of the product. Allow 20-30 days before washing freshly painted surfaces and 30-40 days before washing freshly painted new plaster or concrete surfaces.

APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

TOOL CLEANING

Immediately after use, drain excess paint thoroughly into the container and clean tools using warm soapy water. Do not dispose of washing waste water into the aquifer groundwater.

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

Technical characteristics	Units	Standard	Value
Viscosity	cP	EN ISO 2555	20000 – 26000
pH		ISO 976	8.0 – 9.0
Recoating time	h		24
Drying time	h		2

*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version C: 23/07/2024